

Specifications	Description
System Description:	3 Way system variable curvature
Frequency Response (+3dB -10dB).	de 50 a 20,000Hz.
Horizontal Coverage (-6dB).	100°
Vertical Coverage (-6dB).	Depends on configuration
LF	
Feature:	2X 12" loudspeakers
Frequency range.	From 50 - 400Hz.
Axial Sensitivity (dB SPL, 1 Watt @ 1m)	103 dB.
Power Handling (Watts AES)	1.400
Power Handling (Watts Continuous)	2.800
MAX SPL continuous.	137,5 dB.
MAX SPL (peak).	143,5 dB.
MF	
Feature:	2 X 6" loudspeakers
Frequency range.	From 400 - 2.400Hz.
Axial Sensitivity (dB SPL, 1 Watt @ 1m)	106 dB.
Power Handling (Watts AES)	500
Power Handling (Watts Continuous)	1.000
MAX SPL continuous.	136,0 dB.
MAX SPL (peak).	142,0 dB.
HF	
Feature:	3 x 1" Drivers
Frequency range.	From 2.400 - 20.000Hz.
Axial Sensitivity (dB SPL, 1 Watt @ 1m)	112 dB.
Power Handling (Watts AES)	210
Power Handling (Watts Continuous)	420
MAX SPL continuous.	138,2 dB.
MAX SPL (peak).	144,2 dB.
Enclosure	
Rigging Hardware.	Integrated
Vertical angles range between units	0° / 1,25° / 2,5° / 5° / 10° (Exponential)
Dimensions.	W: 100 cm. H: 38,5 cm. D: 52 cm.
G. Weight	78 kg.
Front Protection	Steel coated grill with special foam filter
Constructed:	Built in Finland Birch plywood
Finish:	Black fine textured Warnex

